

J100 Electric Grease Pump

1. J100 is a plunger grease pump with a discharge pressure of 8 MPa.
2. J100 is suitable for grease grades of NLGI 000, 00, 0, 1, 2#.
3. The pump has three types, cartridge type, removable reservoir type, and fixed reservoir type.
4. Equipped with grease level switch and pressure switch, pressure regulating valve, safety valve and exhaust valve.
5. It is mainly made of aluminum alloy, which is sturdy and durable.
6. It supports a maximum lubrication pipeline of 15 meters.



Specification

Voltage	Discharge	Pressure	Outlets	Cartridges	Reservoirs	Lubricants	Protection	Mounting	Certification
24VDC	15mL/min	Max 8MPa	1 or 2	0.4, 0.7L	0.2~1.5L	NLGI 000~2#	IP65	Upright	CE

Order Code

J100 □ □ □ □ □

- 1 = 1 outlet; 2 = 2 outlets
- 1 = with controller; 0 = external controller
- 1 = With low level switch, 0 = Without low level switch
- 1 = Pressure-relief type; 0 = Progressive type
- 2D = 0.2L detachable reservoir; 3D = 0.3L detachable reservoir; 5D = 0.5L detachable reservoir
- 4C = 0.4L with cartridge; 7C = 0.7L with cartridge; 0C = Cartridge version without cartridge
- 15 = 1.5L fixed reservoir

Dimension

Capacity	H	D
2D	217	59
3D	267	59
5D	356	59
4C	242	117
7C	242	117
0C	242	117
15	320	117

